


4C100-026 Special 4 capacitors in Box



INFO



Other form of the connection on request available

Construction:

Metallized polypropylene film capacitors noninductive type. Self - healing ability. Special plastic case D50mmxL65mm, on request with bottom screw, epoxy resin sealed, Insulated stranded wire leads 0,75mm², the length 60cm, other length or other form of the leads on request available, color differentiation of the leads on request available, flame retards case (UL 94 V-0)

Reference standards:

EN 60252-1
Certificate: by IECEE-CB CZ1596 and CSN-ESČ

Rated voltage: 500V; 400 Hz

Rated capacity: 4x1uF
other capacity on request available

Tolerance: ±20% (M) ±10 % (K)

Climatic category: 40/80/56
according to IEC 60068 – 1

Temperature range: -40°C ÷ +80°C

Dielectric loss at 100Hz: 0,001

Insulation resistance:

Ris > 10GΩ at 20°C,
Um= 100 VDC after 1 min charging

Test voltage between the leads: 1600VDC 2sec
other tests in accordance to IEC 60384-14

Marking for purchase ordering:
4C100-024 4x1 uF ±10% 500V/400Hz

Warning! The manufacturer is not responsible for any damages, caused by the improper installation and application. Before using the capacitor in any application, pleas, read carefully this technical data-sheet.